

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
31 December 2003 (31.12.2003)

PCT

(10) International Publication Number  
**WO 2004/002105 A1**


- (51) International Patent Classification<sup>7</sup>: **H04L 29/06**, G07F 19/00
- (21) International Application Number: PCT/EP2003/005016
- (22) International Filing Date: 14 May 2003 (14.05.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
02013844.2 22 June 2002 (22.06.2002) EP
- (71) Applicant (for all designated States except US): **TELEFONAKTIEBOLAGET LM ERICSSON (PUBL)** [SE/SE]; S-126 25 Stockholm (SE).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **BRANDRUD, Knut** [NO/NO]; Høgdaaveien 5c, N-0680 Oslo (NO). **SCHUBA, Marko** [DE/DE]; Am Schwanenkamp 68, 52457 Aldenhoven (DE). **ZAVAGLI, Guido** [DE/JP]; Nishikata 2-18-12, Bunkyo-ku, Tokyo 113-0024 (JP).
- (74) Agent: **TONSCHEIDT, Andreas**; Ericsson Eurolab Deutschland GmbH, Ericsson Allee 1, 52134 Herzogenrath (DE).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

## Declaration under Rule 4.17:

— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA,

[Continued on next page]

(54) Title: METHOD FOR PROVIDING INFORMATION TO A WEB SERVER



(57) Abstract: The invention relates to a method for providing information related to a client (C) to a first web server (WS 1). The invention further relates to a proxy server, a program unit loadable into a proxy server, a web server, and a program unit loadable into a web sever, all of them to perform the invented method. A second web server (WS2) stores the information related to the client (C), and the first web server (WS 1) is connected to the client (C) via a proxy server (PS). The proxy server stores a cookie for the first web server (WS 1), the cookie being related to the client (C) and the cookie comprising a network address of the second web server (WS2). The client (C) sends a message towards the first web server (WS 1) via the proxy server (PS). The message is received in the proxy server (PS), that inserts the cookie into the message, and forwards the message to the first web server (WS 1). The first web server (WS 1) receives the message, retrieves the network address of the second web server (WS2) from the cookie, and requests the second web server (WS2) for the information related to the client (C). The second web server (WS2) sends information related to the client (C) to the first web server (WS 1).



CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,

GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

**Published:**

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

## **Method for providing information to a web server**

### **Field of invention**

The invention relates to method for providing to a web server information that is related to  
5 a client. The invention further relates to a proxy server, a program unit loadable into a  
proxy server, a web server, and a program unit loadable into a web sever, all of them to  
perform the invented method.

### **Description of prior art**

In the Internet a first web server can be connected to a client for providing a service to the  
10 client. The first web server may demand information related to the client that is held by a  
second web server. An example for the information related to the client is the  
acknowledgement of a mobile payment, that has to be performed before a service can be  
offered to the client by the web server. In this example the second web server can be a  
payment server e.g. a secure electronic transaction wallet server.

15 Further examples are an electronic mail held by an electronic mail server, an authentication  
to be performed by an authentication server, or an electronic ticket that is provided by a  
ticketing server. To access the information related to the client, the IP address of the second  
web server has to be provided to the first web server.

A solution to that problem was proposed in "Card Payment Transactions in an m-  
20 Commerce Environment - Feasibility Study" by Konrad Wrona and Terence Trench,  
Wireless Application Part Forum Meeting, Munich, 10<sup>th</sup> to 15<sup>th</sup> December 2000. According  
to this solution, a mapping is provided between a network address of the client and the web  
address of the second web server in a third web server. This solution poses the problem of  
maintaining the third web server providing the mapping between the network address of the  
25 client and the web address of the second web server. This is especially difficult if the  
number of mappings between network addresses of clients and web addresses of web  
servers is high, and said functionality of mapping between the two address types has to be  
distributed within the network.

Therefore it is subject of the invention to present a simple method to provide information that is related to a client to a web server.

### **Summary of the invention**

This object is achieved by the methods of claims 1, 2 and 5, the proxy server of claim 11, 5 the program unit loadable into a proxy server according to claim 12, the web server according to claim 13, and the program unit loadable into a web server according to claim 14. Advantageous embodiments are described in dependent claims.

It is an advantage of the proposed method that the network address of the second sever is stored in a proxy server and only one proxy server is related to the client. This is 10 advantageous as the network address of the second server can be maintained easily in the proxy server. Further advantageous is, that the network address of the second server is sent during a session between the client and the web server thus avoiding the need of contacting a third web server.

Advantageous is a method wherein the cookie is sent to the proxy server in a session 15 according to a hypertext transfer protocol by the second web server. This is a simple method to provide the network address of the second web server to the proxy server as the second web server is holding its network address.

In another advantageous embodiment the request to the second web server is sent via the client. This is advantageous as the existing session between the client and the web server 20 can be used for sending the request.

A simple method for requesting and providing information related to a client to a web server is especially required if the information authenticates or authorizes the client towards the web server.

### **Brief description of the drawings**

25 Fig. 1 shows an architecture and a signal flow using the invented method and Fig. 2 shows an alternative signal flow using the invented method.

### Detailed description of embodiments

In the following the invention is described in more detail by means of embodiments and figures. Equal reference signs indicate equal elements.

Figure 1 depicts an example of an architecture and a signal flow for using the invented method. It shows a client C connected to a first web server WS1 via a proxy server PS.  
5 Figure 1 further shows a second web server WS2. A message 1 that is sent from the client C to the first web server WS1, a request 2 from the first web server WS1 to the second web server WS2 and a response 3 from the second web server WS2 to the first web server WS1 are depicted as arrows. The contents of the message 1, the request 2 and the response 3 is  
10 described together with the description of the signal flow depicted in figure 2.

Figure 2 depicts an alternative signal flow according to the invention. It shows a client C2 connected to a first web server WS12 and to a second web server WS22 via a proxy server PS2. The alternative signal flow contains a message 12 that is sent from the client C2 to the first web server WS12 via the proxy server PS2, a request 22 that is sent from the first web  
15 server WS12 to the second web server WS22 via the client C2 and a response 32 from the second web server WS22 to the first web server WS12 via the client C2. The message 12, the request 22 and the response 32 are depicted as arrows.

The client C, C2 can be a mobile terminal and the proxy server PS, PS2 can be a wireless application protocol gateway or a hypertext transfer protocol proxy server. The user of the  
20 client C, C2 is requesting a first service from a first service provider that is offering the service via a first web server WS1, WS12. The service can be a service for offering digital content, a service for supplying the user of the client C, C2 with a physical good or any other service. If the service is a service for offering digital content, the first web server WS1, WS12 can be for example a multimedia server storing multimedia streams. The user  
25 of the client C, C2 is subscribed at a second service provider that is offering a further service via a second web server WS2, WS22 to the user of the client C, C2. Said further service can be for example be a service for authentication or authorization or a service for electronic payments. The second web server WS2, WS22 can be for example an electronic mail server, an authentication server, a ticketing server, or a payment server such as a

secure electronic transaction wallet server. The second web sever WS2 can e.g. provide rights related to a service provided by the first server WS1, WS12 to the user of the client C, C2. To this end the second web server WS2, WS22 can store authentication data, electronic tickets, or data related to electronic payments for the user of the client C, C2.

- 5 The client C, C2 establishes a connection to the second web server WS2, WS22 via the proxy server PS, PS2. If the client C, C2 is a mobile terminal and the proxy server PS, PS2 is a wireless application protocol gateway the connection between the client C, C2 and the second web server WS2, WS22 can comprise a first connection between the client C, C2 and the proxy server PS, PS2 over a wireless application protocol and a second connection  
10 between the proxy server PS, PS2 and the second web sever WS2, WS22 over a hypertext transfer protocol. Alternatively the proxy server PS, PS2 can be a hypertext transfer protocol proxy server and the connection between the client C, C2 and the second web server WS2, WS22 can comprise a first connection between the client C, C2 and the proxy server PS, PS2 over the hypertext transfer protocol and a second connection between the  
15 proxy server PS, PS2 and the second web sever WS2, WS22 via the hypertext transfer protocol. To provide connections according to the wireless application protocol to clients of a first kind and connections according to the hypertext transfer protocol to clients of a second kind the proxy server PS, PS2 can provide both the functionality of a wireless application protocol gateway and the functionality of a hypertext transfer protocol proxy  
20 server.

- The second web server WS2, WS22 sends a message containing a cookie to the proxy server PS, PS2 in a session according to the hypertext transfer protocol, the cookie being related to the client C, C2 and the cookie comprising a network address of the second web sever WS2, WS22. The proxy server PS, PS2 stores the cookie for the first web server  
25 WS1, WS12.

The client C, C2 establishes a connection to the first web server WS1, WS12 via the proxy server PS, PS2, for example for receiving digital content from the first web server WS1, WS12.

The first web server WS1, WS12 demands information related to the client C, C2, the information being stored by the second web server WS2, WS22. The information can be for example a ticket allowing access to digital content provided by the first web server WS1, WS12 or information authenticating the user of the client C, C2 towards the first web server WS1, WS12. The information can authorize the user of the client C, C2 towards the first web server WS1, WS12 or the information can be related to a payment for a service, a physical good or digital content that is provided by the first web server WS1, WS12.

The client C, C2 sends a message 1, 12 towards the first web server WS1, WS12 via the proxy server PS, PS2. The proxy server PS, PS2 receives the message 1, 12, inserts the cookie into the message 1, 12 and forwards the message 1, 12 towards the first web server WS1, WS12 for providing the network address of the second server WS2, WS22 to the first web server WS1, WS12. The first web server WS1, WS12 receives the message 1, 12 containing the cookie, retrieves the network address of the second web server WS2, WS22 from the cookie and requests 2, 22 the second web server WS2, WS22 for the information related to the client C, C2. In the alternative signal flow according to figure 2 the request 22 to the second web server WS22 is sent towards the client C2 and redirected or forwarded by the client C2 to the second web server WS22.

The second web server WS2, WS22 sends the information related to the client C, C2 to the first web server WS1, WS12 in a response 3, 32. In the alternative signal flow according to figure 2 the response 32 is sent via the client C2. The first web server WS1, WS12 receives the information related to the client C, C2. The received information can authenticate or authorize the client C, C2 towards the first web server WS1, WS12. According to the information received from the second web server WS2, WS22 the first web server WS1, WS12 can decide to provide a service to the user of the client C, C2. The first web server can e.g. decide to provide access to a digital content, or supply a physical good to the user of the client C, C2 depending on the information received from the second web server WS2, WS22.

In a preferred embodiment of the invention a proxy server PS, PS2 for a communication network using the invented method comprises a memory for storing a cookie, interfaces for

sending and receiving messages, and a processing system that is adapted to receive in a session according to the hypertext transfer protocol a cookie comprising the network address of the second web server WS2, WS22. The processing system is adapted to store a cookie for the first web server WS1, WS12, wherein the cookie is related to the client C, C2  
5 and comprises a network address of the second web server WS2, WS22. The processing system is adapted to receive a message 1, 12 that is addressed to the first web server WS1, WS12, to insert the cookie into the message 1, 12, and to forward the message 1, 12 to the first web server WS1, WS12.

A program unit for use of the proposed method is loadable into a proxy server PS, PS2 in a communication network. The program unit can for example be stored on a data carrier, e.g.  
10 a magnetic or optical recording medium. It can also be embodied as a sequence of signals loadable into a proxy server PS, PS2, e.g. over a data link. The program unit comprises code adapted to store a cookie for a first web server WS1, WS12, wherein the cookie is related to the client C, C2 and the cookie comprises a network address of a second web  
15 server WS2, WS22. The program unit is adapted to process messages, said messages comprising a message 1, 12 for the first web server WS1, WS12 from the client C, C2. The program unit further comprises code adapted to insert the cookie into the message 1, 12 and to forward the message 1, 12 towards the first web server WS1, WS12.

In a preferred embodiment of the invention a web server WS1, WS12 for a communication  
20 network using the invented method comprises interfaces for sending and receiving messages. The web server WS1, WS12 further comprises a processing system that is adapted to retrieve an address of a second web server WS2, WS22 from a cookie and to send a request for information related to a client C, C2 towards the second web server WS2, WS22.

25 A further program unit for use of the proposed method is loadable into a web server WS1, WS12 for a communication network. Said further program unit can for example be stored on a data carrier, e.g. a magnetic or optical recording medium. It can also be embodied as a sequence of signals loadable into a web server, e.g. over a data link. The further program unit comprises code adapted to process messages, said messages comprising a message 1,



12 from a proxy server PS, PS2 and a request 2, 22 towards a second web server WS2, WS22. The message 1, 12 from the proxy server PS, PS2 comprises a cookie with a network address of the second web server WS2, WS22. The request 2, 22 towards the second web server WS2, WS22 demands information related to the client C, C2. The

5 further program unit comprises code adapted to retrieve the network address of the second web server WS2, WS22 from the cookie, and to send the request 2, 22 for information related to the client C, C2 towards the second web server WS2, WS22.

**Claims**

1. Method for providing information related to a client (C; C2) to a first web server (WS1; WS12), wherein a second web server (WS2; WS22) stores the information related to the client (C; C2), and the first web server (WS1; WS12) is connected to the client (C; C2) via a proxy server (PS; PS2), the method comprising the steps of:
  - storing a cookie for the first web server (WS1; WS12) in the proxy server (PS; PS2), the cookie being related to the client (C; C2) and the cookie comprising a network address of the second web server (WS2; WS22),
  - sending a message (1; 12) towards the first web server (WS1; WS12) via the proxy server (PS; PS2),
  - receiving the message (1; 12) in the proxy server (PS; PS2),
  - inserting the cookie into the message (1; 12),
  - forwarding the message (1; 12) to the first web server (WS1; WS12),
  - receiving the message (1; 12) in the first web server (WS1; WS12),
  - retrieving the network address of the second web server (WS2; WS22) from the cookie,
  - requesting (2; 22) from the second web server (WS2; WS22) the information related to the client (C; C2),
  - receiving in the second web server (WS2; WS22) the request (2; 22) for information related to the client (C; C2), and
  - sending (3; 32) information related to the client (C; C2) to the first web server (WS1; WS12).
2. Method for providing information related to a client (C; C2) to a first web server (WS1; WS12), the information being stored by a second web server (WS2; WS22), wherein the first web server (WS1; WS12) is connected to the client (C; C2) via a proxy server (PS; PS2), and wherein the following steps are performed by the proxy server (PS;

PS2):

- storing a cookie for the first web server (WS1; WS12), wherein the cookie is related to the client (C; C2) and comprises a network address of the second web server (WS2; WS22),

- 5      - receiving a message (1; 12) that is addressed to the first web server (WS1; WS12),  
- inserting the cookie into the message (1; 12), and  
- forwarding the message (1; 12) to the first web server (WS1; WS12).

3. Method according to claim 2, wherein the client (C; C2) is a mobile terminal, the proxy server (PS; PS2) is at least one of a wireless application protocol gateway or a hypertext  
10      transfer protocol proxy server, and wherein the connection of the client (C; C2) to the first web server (WS1; WS12) comprises a first connection between the client (C; C2) and the proxy server (PS; PS2) according to a wireless application protocol or a hypertext transfer protocol and a second connection between the proxy server (PS; PS2) and the first web server (WS1; WS12) according to a hypertext transfer protocol.

- 15      4. Method according to claim 2 or 3, wherein the cookie is sent to the proxy server (PS; PS2) in a session according to a hypertext transfer protocol by the second web server (WS2; WS22).

5. Method for requesting by a first a web server (WS1; WS 12) information related to a client (C; C2) from a second web server (WS2; WS22) holding the information related  
20      to the client (C; C2), the method comprising the following steps:  
- receiving a message (1; 12) with a cookie comprising a network address of the second web server (WS2; WS22) from a proxy server (PS; PS2),  
- retrieving the network address of the second web server (WS2; WS22) from the cookie,  
25      - requesting (2; 22) from the second web server (WS2; WS22) the information related to the client (C; C2).

6. Method according to claim 5, wherein the request (22) to the second web server (WS22) is sent via the client (C2).
7. Method according to claim 5 or 6, wherein the first web server (WS1; WS12) receives the information related to the client (C; C2).
- 5 8. Method according to claim 7, wherein the information related to the client (C; C2) authenticates the client (C; C2) towards the web server.
9. Method according to claims 7 or 8, wherein the information related to the client (C; C2) authorizes the client (C; C2) towards the web server.
10. Method according to any of the claims 5 to 9, wherein the second web server (WS2;  
10 WS22) is at least one of a payment server, an electronic mail server, an authentication server, or a ticketing server.
11. Proxy server (PS; PS2) for a communication network, wherein the proxy server (PS; PS2) comprises a memory for storing a cookie, interfaces for sending and receiving messages, characterized by a processing system that that is adapted to perform the  
15 method according to any of the claims 2 to 4.
12. Program unit loadable into a proxy server (PS; PS2) in a communication network, wherein the program unit comprises code adapted to store a cookie for a first web server (WS1; WS12), wherein the cookie is related to the client (C; C2) and comprises a network address of a second web server (WS2; WS22), wherein the program unit is  
20 adapted to process messages, said messages comprising a message (1; 12) for the first web server (WS1; WS12) from the client (C; C2) and wherein the program unit comprises code adapted to insert the cookie into the message (1; 12) and to forward the message (1; 12) towards the first web server (WS1; WS12).

13. Web server in a communication network, comprising interfaces for sending and receiving messages and a processing system that is adapted to retrieve an address of a second web server (WS2; WS22) from a cookie and to send a request for information related to a client (C; C2) towards the second web server (WS2; WS22).
- 5 14. Program unit loadable into a web server in a communication network, wherein the program unit comprises code adapted to process messages, said messages comprising a message (1; 12) from a proxy server (PS; PS2) and a request (2; 22) towards a second web server (WS2; WS22), wherein the message (1; 12) from the proxy server (PS; PS2) comprises a cookie with a network address of the second web server (WS2; WS22), the  
10 request (2; 22) towards the second web server (WS2; WS22) demands information related to the client (C; C2), and wherein the program unit comprises code adapted to retrieve the network address of the second web server (WS2; WS22) from the cookie, and to send the request (2; 22) for information related to the client (C; C2) towards the second web server (WS2; WS22).




Fig. 1




Fig. 2

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 03/05016

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 H04L29/06 G07F19/00

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04L G07F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, INSPEC, COMPENDEX, IBM-TDB

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	MET: "MeT Authorization for account based payment using a SET Wallet Server" MET (MOBILE ELECTRONIC TRANSACTIONS) STANDARD, 'Online! 21 February 2001 (2001-02-21), pages 1-15, XP002221755 Retrieved from the Internet: <URL:http://www.mobiletransaction.org/pdf/MET-SET-Wallet-20010221.pdf> 'retrieved on 2002-11-20!	5-10,13, 14
A	* sections 1., 4., 6.4, 7. * figure 3 ---	1,2,11, 12
X	US 6 157 917 A (BARBER TIMOTHY P) 5 December 2000 (2000-12-05) abstract	2,3,5-14
A	column 6, line 50 -column 7, line 3 --- -/--	1



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

## \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*&\* document member of the same patent family

Date of the actual completion of the international search

4 August 2003

Date of mailing of the international search report

11/08/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Kesting, V



## INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 03/05016

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	"SET Secure Electronic Transaction Specification, Book 1: Business Description" SET SPECIFICATIONS, 31 May 1997 (1997-05-31), XP002100669 page 59 ---	5,13,14
A	US 5 875 296 A (AULT MICHAEL BRADFORD ET AL) 23 February 1999 (1999-02-23) abstract ---	5,13,14
A	WO 01 93092 A (NOKIA NETWORKS OY ;LAHTI JERRY (FI); KERAENEN TUOMAS (FI)) 6 December 2001 (2001-12-06) page 2, line 3 - line 20 ---	1-3,11, 12
A	WO 02 17253 A (SCHUBA MARKO ;WRONA KONRAD (DE); ZAVAGLI GUIDO (JP); ERICSSON TELE) 28 February 2002 (2002-02-28) page 19, line 29 -page 20, line 22 -----	4

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP 03/05016

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 6157917	A	05-12-2000	NONE	
US 5875296	A	23-02-1999	JP 3003997 B2 JP 10257048 A	31-01-2000 25-09-1998
WO 0193092	A	06-12-2001	AU 6397301 A CN 1432161 T EP 1295221 A1 WO 0193092 A1	11-12-2001 23-07-2003 26-03-2003 06-12-2001
WO 0217253	A	28-02-2002	EP 1182625 A1 AU 7851401 A WO 0217253 A1 US 2002052842 A1	27-02-2002 04-03-2002 28-02-2002 02-05-2002